



World Masterpiece Portable Storage Device (PSD)

NEXTO OTG ND 2300



Specifications

- Dimension : 128mm × 77mm × 23mm
- Weight : 130g (without HDD installed)
- LCD Display : 1.15" 2 color FSTN LCD for Text Display
- PC Interface : USB 2.0 (480Mbps)
- Power
 - AC Power Adapter (→ 5V DC, 2A)
 - **USB Bus Power**
- Battery
 - Internal Battery : Li-poly battery (3.7V / 1,550mAh)
 - External Battery (Option) : Li-ion Battery (3.7V / 2,200mAh)

System Requirements

- O/S
 - Windows 98SE/Me/2000/XP
 - Mac OS9.0 or above
 - Linux 2.4.18 or above
- File System
 - HDD : FAT32
 - Memory Card : FAT12/16/32
 - OTG : FAT12/16/32
- Hard Disk Drive
 - Size : 2.5"
 - Type : PATA
 - Volume : **Unlimited**
- Compatible Memory Card
 - CF (Type 1 & 2)
 - MD
 - via 17-in-1 Memory Card Adapter (Option)
 - SD / miniSD
 - XD
 - TransFlash
 - MMC / MMC plus / MMC mobile / RSMC
 - MS / MS MagicGate / MS Select / MS Duo
 - MS Duo MagicGate / MS PRO / MS PRO MagicGate
 - MS Pro Duo / MS PRO Duo MagicGate

Standard Accessories

- USB Cable
- AC Power Adapter
- Pouch
- Screw Driver
- 4 Screws
- Manual

Logistic Information

- Unit Box Size : 240 × 190 × 70mm
- Unit Box Weight : 790g
- Quantity per Carton : 10pcs
- Carton Size : 398 × 255 × 377mm
- Carton Weight : 8.6kg

Products Comparison

		NEXTO OTG		P	Q	R
		OTG	CF			
CF Card Backup Time	SanDisk Ultra-2 CF 1G	2' 50" *	2' 15"	2' 06"	2' 35"	none
	Hitachi MicroDrive 2G	7' 30" *	6' 10"	6' 30"	7' 02"	none
PC Data Transfer Time	via USB Cable ← 2Gbyte	1' 55"		2' 40"	2' 15"	2'
Backup Volume at a full Charge	Internal Battery	variable	35G **	30G	44G	16G
	External Battery	variable		none	none	none
Battery Charging Time	via AC Adapter	3hr 06'		* Tested USB Slave Device: i-Lock USB Card Reader ** Tested Memory Card : SanDisk-2 CF 1G		
	via USB Cable	4hr 37'				

How to back up your Data



DISTRIBUTED BY :
 TECHNOBOX AUSTRALIA - 28 PEEL STREET - MITCHAM - 3132 - VICTORIA - AUSTRALIA
 PH : (61) (03) (8802 4999) - ONLINE STORE : www.technobox.com.au